

Code	Description	Size	Colour
20079	Gorilla Manhole Sealant	16mm x 3.8mr	Grey
20197	Gorilla Manhole Sealant	20mm x 3.8mr	Grey

1. Description

Is a butyl rubber sealing tape for non-critical sealing and glazing application in drainage system. Provides economical installation because of its form and ease of handling.

2. Characteristics

- It has some degree of pressure sensitivity and is sufficiently soft for ease of compression during installation
- It has good weather and ageing resistance
- It is relatively flexible and does not harden
- It does not stain

3. Technical Data

Appearance:	Light grey compound
Needle Penetration:	40-60
Specific Gravity:	1.70-1.80
Shear Strength:	0.80-1.30kgf/1.5cm ²
Peel Adhesion:	0.20-0.50 kgf/6mm
Tensile Strength:	0.25 - 0.70 kgf/cm ²
Water Absorption:	<1.00%

4. Applications

- Ready to use as tape sealer, reeled up with release paper
- It is pre-cut at a fixed length
- Peel off the tape from the release paper and simply apply
- Area of application must dry, clean, free from dirt and oil
- Application temperature ranges from 5°C to 40 °C

5. Packaging

16mm x 3.8m

6. Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

7. Application Instructions

Method: Peel of the tape from the release paper and simply apply.
Place Gorilla Manhole Sealant on top of pipe and firmly position second pipe on top.

Application Temperature: +5°C and +40°

Clean: Ensure surface is clean, dry, free of dust and grease.

Soudal recommends preliminary compatibility tests to ensure that the user is satisfied with the result given.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene
- Please refer to the MSDS for more detailed information.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email sales@soudal.co.nz.***

Last Updated: 21 November 2019

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	Fax: (07) 847 0324
	Hamilton 3200	Email: info@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz