

Code	Description	Size	Colour
01471	Gorilla Linseed Putty	1kg	Natural beige

## 1. Description

Gorilla Linseed Window Putty is a high quality filler and sealant based on linseed oil modified with synthetic resins.

## 2. Characteristics

- Ideal for window frames
- High quality filler
- Paintable
- Suitable for timber, concrete and metals
- Easy to knead

## 3. Technical Data

<b>Base:</b>	Linseed Oil
<b>Consistency:</b>	Paste
<b>Curing System:</b>	Oxidation
<b>Shrink</b>	None
<b>Density (DIN 53479 B)</b>	2.1g/ml
<b>Temperature Resistance</b>	-20°C until +80°C
<b>Maximum allowed movement</b>	5%

*\*This varies according to ambient conditions such as temperature, humidity, substrate etc*

## 4. Applications

- Installation of glass sheets
- Repair of glazing which has been sealed with window putty
- Installation of glass sheets in greenhouses and verandas

## 5. Packaging

Plastic pots of 1kg

## 6. Shelf Life

12 months in unopened container in a dry and cool storage area at temperatures of between +5°C and +25°C.

## 7. Application Instructions

### Surfaces

Type:

Timber, concrete and metals

Surfaces must be clean and sound, dry and free from dirt and grease.

We recommend to apply a layer of varnish or primer prior to application.

Soudal recommends a preliminary compatibility test.

**Joint Dimensions:**

Minimum: 10mmx10mm  
Maximum 20mmx15mm

**Application:**

Application method: Apply with a spatula  
Application Temperature: +5°C until +30°C  
Clean with water and soap immediately after application  
Finish with a spatula  
Repair damage with window putty

**Warning: Product has limitations. Please ensure when using this product that you read the instructions carefully. Soudal recommends to test prior due to the diversity of substrates and applications that are out of Soudal's control. Soudal cannot accept accountability for adverse results.**

**8. Health and Safety Recommendation**

- Apply the usual industrial hygiene.
- Please refer to MSDS for more detailed information

**Remark**

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email [sales@soudal.co.nz](mailto:sales@soudal.co.nz).***

**Last Updated:** 29 July 2019

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	Fax: (07) 847 0324
	Hamilton 3200	Email: <a href="mailto:sales@soudal.co.nz">sales@soudal.co.nz</a>
	New Zealand	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>