

Code	Description	Size	Colour
01493	Gorilla Carpet Gripper	500ml	Brown

1. Description

Gorilla Carpet Gripper is a one component, ready to use Polyurethane based adhesive with excellent water resistance.

2. Characteristics

- Easy application
- Professional quality
- Foaming penetration action to fill bond cavities
- Fast drying
- Water resistance: D4 (DIN EN 204)
- Can be used on damp wood

3. Technical Data

Base:	Polyurethane
Consistency:	Liquid
Curing System:	Moisture Cure
Open Time(*):	5 min.
Clamping Time:	At least 30 minutes
Compression Strength:	Ca. 1 kg/cm ²
Density (DIN 53479):	1,1 g/mL
Water Resistance (according to DIN EN 204):	D4
Temperature Resistance:	-30°C to +100°C
Shear Strength:	> 10 N/mm ²
Solid Content:	95%
Coverage:	Ca. 150 mL/m ²

*This varies according to ambient conditions such as temperature, humidity, substrate etc

4. Applications

- Interior applications with frequent long-term exposure to running or condensed water.
- Exterior applications with exposure to weather influences.
- Manufacturing of door and window-frames that need to meet class D4 according to EN204.
- Bonding of wooden construction elements.

5. Packaging

Plastic Sauce Bottle 500ml

6. Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

7. Application Instructions

Surfaces

Type:	Various porous and non-porous substrates such as wood, concrete, bricks and other common materials in the building industry. Not suitable for PE and PP.
State of Surface:	Clean, free of dust and grease.
Preparation:	The adhesive cures under the influence of humidity. Slight moistening of the substrate(s) improves curing rate and gap filling characteristics as adhesive foams up to penetrate cavities.

Soudal recommends a preliminary compatibility test.

Application

Method:	Apply the adhesive by means of a brush or notched trowel to one of the materials to be bonded. Join the parts together within 5 minutes and clamp for at least 30 minutes. Pressing the materials, during curing, is necessary to reach the highest possible end strength.
Application temperature:	+5°C to +35°C.
Cleaning:	Uncured Gorilla Carpet Gripper can be removed from tools and materials with Gorilla Expanding Foam Cleaner. Cured adhesive has to be removed mechanically.
Repair with:	Gorilla Carpet Gripper.

Warning: Product has limitations. Please ensure when using this product that you read the instructions carefully. Soudal recommends to test prior due to the diversity of substrates and applications that are out of Soudal's control. Soudal cannot accept accountability for adverse results.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene.
- Please refer to MSDS for more detailed information

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.***

Last Updated: 29 September 2020

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz