

| Code  | Description                          | Size   | Colour    |
|-------|--------------------------------------|--------|-----------|
| 01532 | Holdfast Fast Finish Wallpaper Paste | 2 Kg   | Off White |
| 01534 | Holdfast Fast Finish Wallpaper Paste | 500 gm | Off White |

## 1. Description

Holdfast Fast Finish Wallpaper Paste is a highly refined and purified Sodium Carboxymethylcellulose. It is tasteless, odourless.

## 2. Characteristics

- Handles all normal wallpapers and paper backed vinyl's
- Easy mixing & no lumps
- Thickens rapidly, ready in 10-15 minutes
- Good slip slide action
- Contains an efficient fungicide and is non-staining

## 3. Technical Data

|  |                       |
|--|-----------------------|
| <b>Smell:</b>  | Odourless             |
| <b>Taste:</b>  | Tasteless             |
| <b>Colour:</b>   | White Cream Powder    |
| <b>NaCMC content (dry basis):</b>                      | Min 99.50%            |
| <b>Moisture as Packed:</b>                             | Max 10.00%            |
| <b>Sodium Chloride content (dry basis):</b>            | Max 0.50%             |
| <b>Sodium Glycolate content (dry basis):</b>           | Max 0.40%             |
| <b>Degree of Substitution:</b>                         | 0.75 – 0.85           |
| <b>Sodium content:</b>                                 | 7.5 – 9.0             |
| <b>Sulphated Ash content</b>                           | 23.0 – 27.0           |
| <b>pH (1% solution)</b>                                | 6.5 – 8.0             |
| <b>Viscosity, 1%, 25°C</b>                             | 2500 – 3500m          |
| <b>Brookfield LVT</b>                                  | 0.4 N/mm <sup>2</sup> |
| <b>Typical Particle size &gt; 0.075:<br/>&gt;1.5mm</b> | Min 85%<br>Max 0.5%   |
| <b>Application Temperature:</b>                        | +10°C → 30°C          |

*\*This varies according to ambient conditions such as temperature, humidity, substrate etc*

## 4. Applications

Holdfast Fast Finish Wallpaper Paste will bond to most surfaces provided they are clean and dry.

However, as a result of a natural process the viscosity of cellulose gum may decrease in time. We guarantee that the product will meet the viscosity specification for 12 months after the indicated "Manufacturing Date". After these 12 months the products can still be used safely up to the indicated shelf life end date, but may need a slight dosage correction in order to give optimum performance in the application.

**Warning: Product has limitations. Please ensure when using this product that you read the instructions carefully. Holdfast recommends to test prior due to the diversity of substrates and applications that are out of Holdfast's control. Holdfast cannot accept accountability for adverse results.**

## 5. Packaging

500 gr and 2Kg

## 6. Shelf Life

36 months

## 7. Application Instructions

**Preparation:** All surfaces must be sound, clean, dry and free from mould growth. Remove all existing wallpapers, lining papers and previous wallpaper paste. Walls should be washed with Holdfast Sugar Soap. Any holes or cracks should be filled with Holdfast Gorilla PRO Gaps Interior.

### **Checking Existing Sealed and Painted Surfaces**

With a clean cloth rub surface of paint 5 to 10 times with Holdfast Methylated Spirits. If paint is removed it is probably plastic paint. Paint resistant to methylated spirits is generally oil based enamel. Paints soluble in water are usually cheap kalsomine or similar types and should be removed. Sandpaper, gloss and semi gloss enamel surfaces to assist adhesion.

Cut a small X in the paint with a sharp blade. Vary height of the X, and test every lineal metre of length of each wall. Stick a piece of tape firmly over each X, then pull tape off quickly. If tape pulls off paint from X then paint adhesion is suspect and may need to be removed with Holdfast Strip-It-Off.

### **Bare Surfaces & Plastic Paints**

New plasterboard, masonite cement render, cement sheeting and paints sensitive to methylated spirits should be sealed with a good quality oil based sealer as maker directs.

### **Estimated Coverage\* Use as a guide only**

| Size                  | Water     | Coverage                     |
|-----------------------|-----------|------------------------------|
| 300g Size (50gm/L)    | 6 Litres  | 20 rolls / 120m <sup>2</sup> |
| 250g Paste (12.5gm/L) | 20 Litres | 20 rolls / 120m <sup>2</sup> |

### **For Sizing Application**

- Measure the surface areas to be sized. If the full pack is not required at once calculate the amount of Holdfast Wallpaper Size needed for the job. \*50 grams added to 1 litre of cold water will cover approx. 20m<sup>2</sup>
- Place correct amount of water required into a clean bucket.
- Sprinkle powder into water whilst stirring briskly.
- Leave for 10-15 minutes, stir again and your size is ready to apply.
- Apply generously to the prepared surfaces with a broad brush or roller, ensuring even coverage.
- Allow 2-3 hours drying time before hanging wallpaper.

### **For Pasting Application**

- Ensure paste bucket and utensils are perfectly clean.
- For standard type papers, into 4 litres of cold water quickly sprinkle 50grams of powder whilst stirring briskly. (Heavy weight papers require a thicker paste plus longer soak time. Therefore use less water in your mix.)
- Leave for 10-15minutes, stir again and your paste is ready to use.
- Apply evenly to paper, ensuring edges are fully pasted.
- Any excess paste should be removed while still wet with a damp, clean cloth.

**Note:** Never hang wallpaper on damp surfaces, or when temperature is greater than 30°C or lower than 10°C.

*Soudal recommends preliminary compatibility tests on surfaces on which Holdfast Fast Finish Wallpaper Paste has not been applied previously.*

## 8. Regularity Compliance

Holdfast Fast Finish Wallpaper Paste complies with the requirements contained in the following regulations and standards. Food Chemicals Codex, 21 CFR 182. 1745, JECFA, the purity criteria in the current EC Directive, Japan's Specifications and Standards for Food Additives, and the National Standard of the People's Republic of China. Billsticker Poster PASTE also conforms to the monographs of "Camellose Sodium" or "Carboxymethylcellulose Sodium" in the current Ph. Eur, USP/NF, JP, and several local pharmacopeia's

## 9. Health and Safety Recommendation

- Text

**Remark**

The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email [info@soudal.co.nz](mailto:info@soudal.co.nz).**

**Last Updated:** 1 February 2022

|  |                 |   |
|--|-----------------|---|
| Recommended use:                                     |                 |   |
| HSNO Group Standard                                  |                 |   |
| UN number, shipping name and packaging group:        |                 |   |
| Supplier contact details:                            | Soudal Ltd      | Freephone: 0800 70 10 80  |
|  | 14 Avalon Drive | Phone: (07) 847 5540  |
|  | Nawton          |   |
|  | Hamilton 3200   | Email: <a href="mailto:info@soudal.co.nz">info@soudal.co.nz</a> |
|  | New Zealand     | Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a> |
| <b>POISON CENTRE NUMBER: 0800 764 766 (24 hours)</b> |                 |   |