

Code	Description	Size	Colour
19920	Gorilla Silicone Remover Hangsell	100ml	Clear

1. Description

Sealant Remover is a ready-made gel for the easy removal of cured silicones and MS-Polymers.

2. Characteristics

- Ready to use, no mixing required
- Liquid, easy application
- Non-sagging
- Suitable for silicone and MS-polymer sealants

3. Technical Data

Base	Mixture of terpenes
Curing System	Chemical curing
Consistency	thixotropic gel
Density	0,875 g/mL
Viscosity	1400 ±600Poise
solubility in water	Soluble
solubility in	soluble in hydrocarbons

4. Applications

Removal of cured silicone and MS-polymer sealants from all sorts of substrates.

5. Packaging

100ml Plastic container

6. Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°.

7. Application Instructions

Surfaces

Type: all non-porous surfaces (not on nylon and PMMA)

Soudal recommends preliminary compatibility tests.

Application

Application method: The substrates should be dry before applying the Sealant Remover. Do not apply when rain is imminent. Cut away as much as possible from the old sealant with a sharp knife, apply the Sealant Remover on the remains and leave it there for at least 10minutes. Remove the remains then with a spatula or cloth and check whether all residues have gone. If not repeat the whole process.

Application temperature: +5 to +30°C

Cleaning: white spirit.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene.
- Wear gloves and goggles.
- Apply only in a ventilated area.
- In case of contact with skin, wash with water and soap.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz***

Last Updated: 7 July 2020

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz