

Code	Description	Size	Colour
19921	Gorilla Expanding Foam Remover	100ml	N/A

1. Description

Gorilla Expanding Foam Remover is a ready to use gel for the easy removal of all remains of cured Gorilla Expanding Foams. **NOTE:** Testing for compatibility to non-porous surfaces is essential.

2. Characteristics

- Very Active
- Odourless
- Free of (aromatic) hydrocarbons
- Easily biodegradable
- Economic & easy to apply
- Solvent free

3. Technical Data

Base:	Water Soluble Solvents
Consistency	Gel
Density	Approx. 1.54 +/- 0.05 g/cm ³
Solubility in Water	Soluble
pH 10% in water	Approx. 10.5
Colour	Off White
Application Temperature	+5°C to +35°C

**This varies according to ambient conditions such as temperature, humidity, substrate etc*

4. Applications

- Easily removes all cured Expanding Foam residues on non-porous surfaces such as plastics, metals & PVC etc.

5. Packaging

Cartridge of 100ml

6. Shelf Life

At least 36 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

7. Application Instructions

Surfaces

- Type: Non-Porous surface such as Plastics, metals & PVC etc
Test product in unobtrusive area first to ensure that you do not get an unexpected colour change in the surface
Do Not Use Gorilla Expanding Foam Remover on untreated Copper, Brass, Zinc, Acrylic Paints or PMMA (Plexiglass)
- State: Clean, free of dust and grease
- Preparation: We recommend a preliminary compatibility test on an invisible part of the substrate.
Gorilla Expanding Foam Remover may cause staining on porous surfaces (such as natural stone)
- Method: Remove mechanically or cut away carefully as much cured foam as possible.
Apply Gorilla Expanding Foam Remover by means of the enclosed brush onto the cured PU foam.
Leave Gorilla Expanding Foam Remover for at least 30 minutes and maximum 2 hours.
Remove dissolved foam with the enclosed spatula and wipe off with a dry cloth.
If necessary, repeat treatment by reapplying PU remover.

Application

- Method: Brush supplied in packet
- Application Temperature: +5°C to +35°C
- Clean: Water once excess moved from surface

Limitations

- Do Not Use Gorilla Expanding Foam Remover on untreated Copper, Brass, Zinc, Acrylic Paints or PMMA (Plexiglass)
- Gorilla Expanding Foam Remover may cause staining on porous surfaces (such as natural stone)

Soudal recommends preliminary compatibility tests on surfaces on which Gorilla Expanding Foam Remover has not been applied previously.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene
- Please refer to the MSDS for more detailed information.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email sales@soudal.co.nz.***

Last Updated: 10 February 2021