

Code	Description	Size	Colour
20016	Holdfast 899.050 Solvent	20 Litre	N/A

1. Description

HOLDFAST® 899.050 Solvent is a solvent blend, which has been designed for the cleaning and removal of dried solvent based adhesives.

2. Characteristics

- Extra quick evaporation
- Excellent clean up
- Removes grease marks

3. Technical Data

Appearance:	Clear Liquid
Viscosity:	Solvent Thin
Solids:	Less Than 1%
Specific Gravity:	Approx. 0.78

4. Applications

- Cleaning Equipment
- Removing adhesive spillage

5. Packaging

20 Litre

6. Shelf Life

24 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25° in unopened containers.

7. Application Instructions

Method: Apply solvent to equipment or spillage and wipe away using a fabric cloth or rag. Ensure that solvent soaked materials are disposed of in accordance with federal and local disposal regulations.
As a thinner, HOLDFAST® 899.050 Solvent may be used in the thinning down of brush or roller grades of Neoprene contact adhesives. Add small quantities of solvent blend to the adhesive until the adhesive viscosity meets application requirements. Thinning of adhesive will generally cause the drying time to increase.

Application Limitations HOLDFAST® 899.050 Solvent is not recommended to be used for the thinning of spray able Neoprene contact grades.
HOLDFAST® 899.050 Solvent is not suitable for adhesives used to bond Polystyrene foam, since attack of the foam will occur

- Test is always best as although initial tests have been completed and show no effect, we cannot guarantee this for all surfaces.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene
- Please read the Material Safety Data Sheet for this product BEFORE it is used.
- Keep product away from all possible sources of ignition.
- Store material between 15°C and 30°C, away from sources of heat and direct sunlight.
- If the product is classed as a dangerous good, ensure that the product is stored in compliance with the applicable dangerous goods storage regulations.
- Refer to the products Material Safety Data Sheet for the dangerous goods classification.

- We highly recommend a preliminary compatibility test.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.***

Last Updated: 27 August 2021

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz