

Code	Description	Size	Colour
20057	Gorilla Primer 150	500ml	Transparent

## 1. Description

Gorilla Primer 150 is a universal primer for porous surfaces to be used with silicone sealants and sealants based on MS Polymers.

## 2. Characteristics

- Liquid, easy application
- Suitable for silicones and MS Polymers based sealants and adhesives

## 3. Technical Data

<b>Base:</b>	Synthetic resins
<b>Consistency:</b>	Liquid
<b>Curing System:</b>	Physical drying
<b>Skin Formation (20 °C/65% R.H):</b>	Ca. 60min.
<b>Specific Gravity (DIN 53479B):</b>	0,93 g/ml
<b>Flashpoint:</b>	8°C
<b>Quantity to be applied:</b>	Ca. 5m2/L

## 4. Applications

- All Porous Surfaces
- Joint sides of expansion joints (Horizontal or Vertical)
- Joint sides of porous materials (surfaces) exposed to water pressure.

## 5. Packaging

500ml alu bottle

## 6. Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°. Protect against frost.

## 7. Application Instructions

*Method:* brush  
*Application temperature:* +5°C to +35°C  
*Clean:* with white spirit immediately after application  
*Recommendation:*  
 after application of Primer 150, wait 60 minutes at least and 4 hours at most before applying a sealant.

## 8. Health and Safety Recommendation

- Apply the usual industrial hygiene
- Please refer to the MSDS for more detailed information.

**Remark**

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email [sales@soudal.co.nz](mailto:sales@soudal.co.nz).***

**Last Updated:** 29 July 2019

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	Fax: (07) 847 0324
	Hamilton 3200	Email: <a href="mailto:sales@soudal.co.nz">sales@soudal.co.nz</a>
	New Zealand	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>