

Code	Description	Size	Colour
21408	Holdfast Hot Melt Glue Stick Mini 118PK 1kg	7.2mm x 200mm	Translucent
21411	Holdfast Hot Melt Glue Stick Mini 10PK	7.2mm x 200mm	Translucent
21414	Holdfast Hot Melt Glue Stick Mini 590PK 5kg	7.2mm x 200mm	Translucent

1. Description

Holdfast Hot Melt Glue Stick is a translucent, high viscosity and slow setting general purpose translucent glue stick.

2. Characteristics

- High Viscosity
- General purpose
- Slow Setting
- Excellent clarity after application

3. Technical Data

Base :	Synthetic Resin (Ethylene Vinyl Acetates)
Colour :	Translucent
Softening Point :	80°C
Set Time :	15 – 20 seconds
Water Resistance :	Excellent
Application Temperature :	160°C – 190°C

**This varies according to ambient conditions such as temperature, humidity, substrate etc*

4. Applications

- It is recommended for the bonding of many material types such as paper, card, cloths & plastics
- Meets the requirements of in-direct food additives regulations **21 CFR 175.105 – Adhesives**

5. Packaging

10pk, 30pk, 52pk, 260pk

6. Shelf Life

24 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +30°C. Keep out of direct sunlight and away from sources of heat.

7. Application Instructions

Surfaces: Paper, Card, Cloth, Plastics, .
State of Surface: Clean, dry and free of dust and grease.

Application

Method: Use with the Gecko Hot Melt Glue Gun

Precaution : Keep unused adhesives in a closed carton and away from dusty areas.
Glue applicator gun is hot, avoid touching any part of the application gun other than its glue tank handle when adding new glue sticks.

Due to the range of products available, Soudal recommends preliminary compatibility testing prior to application.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene.
- Please refer to MSDS for more detailed information

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.***

Last Updated: 5 May 2020

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	Fax: (07) 847 0324
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz