

Code	Description	Size	Colour
37020	Holdfast Mineral Turpentine	1 Lt	Clear
37025	Holdfast Mineral Turpentine	4 Lt	Clear

## 1. Description

FastFinish Mineral Turpentine is a versatile chemical and industrial solvent useful in many secondary industries. Mineral Turpentine is often a component of cleaning chemicals, construction coatings and general paint thinners. Mineral Turpentine has a distinguished odour and combines easily with petroleum solvents.

## 2. Technical Data

Characteristics	Test Methods	Specification
Appearance:	Visual	Clear, colourless liquid, free of particles
Colour, Saybolt	ASTM D156	25
Specific Gravity (@ 15°C):	ASTM D1298	0.81-0.82 g/ml typical
Flash Point:	ASTM D93	41°C
Boiling Range:	ASTM D86	
IBP		154°C
50%		167°C
DP		192°C
Aniline Point:	ASTM D611	23°C typical
Refractive Index	ASTM D1747	1.458 minutes
Residue on Evaporation:	ASTM D1353	20Ppm

*\*This varies according to ambient conditions such as temperature, humidity, substrate etc*

## 3. Other Characteristics

- The product is not miscible with water

## 4. Health and Safety Recommendation

- Apply the usual industrial hygiene
- Please refer to the SDS for more detailed information

### Remark

The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email [info@soudal.co.nz](mailto:info@soudal.co.nz).**

**Last Updated:** 20 April 2021

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: <a href="mailto:sales@soudal.co.nz">sales@soudal.co.nz</a>
	New Zealand	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>