

#### TECHNICAL DATASHEET

Code	Description	Size	Colour
56215	Gorilla Paint Masker Cloth Tape with Film	1200mm x 25mr	Green / Clear
56216	Gorilla Paint Masker Cloth Tape with Film	1800mm x 25mr	Green / Clear
56217	Gorilla Paint Masker Cloth Tape with Film	2400mm x 25mr	Green / Clear
56218	Gorilla Paint Masker Cloth Tape with Film	610mm x 25mr	Green / Clear

### 1. Description

Paint Masker Cloth Tape with Film is a pre-taped film designed to provide fast and easy application. Perfect for taping edges before applying paint, providing for 45 day clean removal without leaving an adhesive residue.


#### 2. Characteristics

- · Designed for high build coatings
- · No stretch
- · Superior strength
- · 45 day clean removal

## 3. Technical Data

Tape Backing:	Low Density Polyethylene	
Adhesive:	Transparent Rubber Solvent Based	
Film material:	100% HDPE (natural colour)	
Normal Exterior Usage: *	Up to 45 days	
Total Tape Thickness:	300 microns	
Film Thickness:	0.025mm, ±0.002mm	
Tensile Strength:	45 N/25mm	
Adhesion to Steel	4.2N/25mm	
Application Temperature: *	12°C to 25°C	
Storage Temperature:	12°C to 25°C	
In Service Temperature:	-10°C to +60°C	

### Structure:



### General property:

Test item	Unit	At temp. (deg. C)	Value
		-10	12.24
Adhesion to steel	N/10mm	0	7.29
		23	2.94
		-10*1)	3
Tools	Ball No.	0*2)	14
Tack		23*2)	44
		23*3)	26
Tensile strength	N/10mm	23	51

### Note:

- \*1) = ball rolling down slope at 5
- \*2) = ball rolling down slope at 15
- \*3) = ball rolling down slope at 30

### Test Method: JIS Z 0237

- \*Specification is subject to change without notice.
- \*All the figures, technical information and recommendation stated above are on the basis of the tests we believe to be reliable, but the accuracy thereof is not guaranteed.

# 4. Applications

General purpose masking.

#### 6. Shelf Life

1 year from the day of purchase. Store unopened in cool and dry location.

## 7. Application Instructions

State: Thoroughly clean and dry surfaces.

Type: All usual building substrates

State: Porous surfaces should be primed with Primer 150, Surface Activator may be used on non-porous surfaces.

Soudal recommends preliminary compatibility tests prior to application.

### **Application**

The adhesive is pressure sensitive. The more pressure, the more adhesion power will be obtainable. Dependent

upon what type of material

To be adhered to, adhesive may be deposited on surface, especially for marble or PVC materials. When this tape

is to be peeled off, do so slowly.

Do not apply to skin or use as electric insulation.

#### 8. Health and Safety Recommendation

· Apply the usual industrial hygiene.

#### Remark

The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.

Last Updated: 30 November 2024

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	134 Kohia Drive	Phone: (07) 847 5540
	Horotiu	
	Hamilton 3288	Email: info@soudal.co.nz
	New Zealand	Website: <u>www.soudal.co.nz</u>