

Code	Description	Size	Colour
56231	Gorilla Paint Masker Cloth Tape	18mm x 25mr	Green

1. Description

Paint Masker Cloth Tape is superior in durability and weather resistance, performs in all weather conditions. It is UV resistant and does not leave residue when exposed to high temperatures. It does not tear or remain adhered to application surface even under low temperatures.

2. Characteristics

- Designed for high build coatings
- No stretch
- Superior strength
- 45 day clean removal

3. Technical Data

Structure:



General property:

Test item	Unit	At temp. (deg. C)	Value
Adhesion to steel	N/10mm	-10	12.24
		0	7.29
		23	2.94
Tack	Ball No.	-10*1)	3
		0*2)	14
		23*2)	44
		23*3)	26
Tensile strength	N/10mm	23	51

Note:

- *1) = ball rolling down slope at 5
- *2) = ball rolling down slope at 15
- *3) = ball rolling down slope at 30

Test Method: JIS Z 0237

*Specification is subject to change without notice.

*All the figures, technical information and recommendation stated above are on the basis of the tests we believe to be reliable, but the accuracy thereof is not guaranteed.

4. Applications

General purpose masking.

6. Shelf Life

1 year from the day of purchase. Store unopened in cool and dry location.

7. Application Instructions

State: Thoroughly clean and dry surfaces.
Type: All usual building substrates
State: Porous surfaces should be primed with Primer 150, Surface Activator may be used on non-porous surfaces.
Holdfast recommends preliminary compatibility tests prior to application.

Application

The adhesive is pressure sensitive. The more pressure, the more adhesion power will be obtainable. Dependent upon what type of material
To be adhered to, adhesive may be deposited on surface, especially for marble or PVC materials. When this tape is to be peeled off, do so slowly.
Do not apply to skin or use as electric insulation.

8. Health and Safety Recommendation

· Apply the usual industrial hygiene.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.***

Last Updated: 14 November 2024

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	134 Kohia Drive	Phone: (07) 847 5540
	Horotiu	
	Hamilton 3288	Email: info@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz