

Code	Description	Size	Colour
56659	Gator SP Surface Protection Tape	96mm x 50mr	Black

1. Description

Gator SP Surface Protection Tape is a high performance LDPE tape with rubber solvent adhesive.

2. Characteristics

- 100 micron backing provides good protection from heavy knocks and scrapes.
- Good UV resistance
- Good elongation and conformability.

3. Technical Data

Backing:	Low Density Polyethylene
Adhesive:	Transparent Rubber Solvent Based
Normal Exterior Usage: *	Up to 45 days
Total Tape Thickness:	120 microns
Tensile Strength:	45 N/25mm
Adhesion to Steel	4.2N/25mm
Application Temperature: *	12°C to 25°C
Storage Temperature:	12°C to 25°C
In Service Temperature:	-10°C to +60°C

4. Applications

- Used as a temporary Exterior/Interior Protection Film designed to protect the surface of delicate building materials.
- Provide temporary protection for aluminium profiles.

5. Packaging

Per Roll (96mm x 50m)

6. Shelf Life

12 months if stored in cool, dry place in original carton at 23°C and 65% relative humidity.

7. Application Instructions

Surfaces

State: Clean, dry and free from grease and dust.

Preparation: Pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels.

Limitations: Due to the number of different substrates and finishes in the market, Soudal recommends preliminary compatibility testing to ensure that you will achieve your desired result.
Not designed to be used on a two way material.

8. Health and Safety Recommendation

- Apply the usual industrial hygiene.
- Pre-testing for adhesion is intended to eliminate potential field problems. This testing will aid in determining the proper surface preparation method.
- For more detailed information, please refer to the SDS.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.***

Last Updated: 23 May 2025

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	134 Kohia Drive	Phone: (07) 847 5540
	Horotiu	
	Hamilton 3288	Email: info@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz