

Code	Description	Length	Colour	Size
63003260	Slimline PVC Glasstrack (pair)	4.7mm 3.6m	White	5 pk
63031261	Slimline PVC Glasstrack (pair)	6.3mm x 1.2m	White	5 pk
63032261	Slimline PVC Glasstrack (pair)	6.3mm x 1.5m	White	5 pk
63033261	Slimline PVC Glasstrack (pair)	6.3mm x 1.8m	White	5 pk
63035261	Slimline PVC Glasstrack (pair)	6.3mm x 2.4m	White	5 pk
63036261	Slimline PVC Glasstrack (pair)	6.3mm x 3.6m	White	5 pk

1. Description

Slimline PVC Glasstrack (sold in pairs) twin rail designed for glass up to 6mm thickness.

2. Characteristics

- Interior/Exterior Rigid profile extrusion
- Lead Free compound

3. Technical Data

Type:	Interior/Exterior Rigid profile extrusion
Hardness: (ASTM D2240 – Shore @23°C)	D80 ± 2
Specific Gravity: (ASTM D792)	1.42 ± 0.02
Tensile Strength: (ASTM D412)	44 Nmm-2
Elongation @ Break: (ASTM D412)	98%
Impact Strength: (ASTM D3029)	9 Joule
Impact Strength – IZOD: (ASTM D256 Method A)	n/t Joule
Vicat Softening Point : (852782 pt 120A)	74 °C
Deflection Temperature @ 1.8MPa: (ASTM D648)	n/t °C
Titanium Dioxide:	8.5phr <

4. Limitation

Dark colours are not suitable for exterior use.

5. Packaging

Plastic Slimline Bag, 5pair per bag (10 pieces)

Remark

The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.**

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: info@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz

Last Updated: 24 March 2022