

Code	Description	Size	Colour
72258	Holdfast WD-40 Penetrating Aerosol	300gm	Light Amber

1. Description

Holdfast WD-40 Penetrating Aerosol is a high quality penetrating oil designed to lubricate moving parts. It protects against rust and corrosion. It penetrates to free stuck corroded parts.

2. Characteristics

- Highly efficient in releasing corroded and rusted metal parts such as nuts, bolts and machine parts
- Due to the very low surface tension Gorilla Penetrating Spray penetrates into very small openings to release stuck parts
- Can be used with machinery, nuts, bolts, flanges, etc.
- Displaces moisture
- May remove some adhesive, corrosion, paint

3. Technical Data

Base:	Mixture of mineral oils
Consistency:	Liquid
Specific Gravity:	0.80-0.82
Flash point:	49°C
Solubility in water:	Insoluble
VOC content:	70-75%%

Property	Test Method	Results
Lubricates & Protects	ASTM 4172	0.60-0.70 mm at RT
Extreme Pressure Lubrication	ASTM3233	590-907lbs
Corrosion Protection (Salt Spray)	ASTM B-117	0-20% in 72 Hours

4. Applications

- Highly efficient in releasing corroded and rusted metal parts such as nuts, bolts and machine parts
- Due to the very low surface tension Gorilla Penetrating Spray penetrates into very small openings to release stuck parts
- Can be used with machinery, nuts, bolts, flanges, etc.

5. Packaging

Canister of 300gm (net content)

6. Application Instructions

- Remove dirt and loose rust mechanically by means of a metal brush.
- Shake can thoroughly before application.
- Apply onto surface and leave to penetrate during ca 5-10 minutes.
- Repeat if necessary

Soudal recommends preliminary compatibility tests on surfaces on which PU Foams have not been applied previously.

8. Health and Safety Recommendation

- Apply only in a ventilated area.
- In case of contact with eyes, wash immediately with plenty of water.

Remark

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email info@soudal.co.nz.***

Created: 8 March 2021

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	14 Avalon Drive	Phone: (07) 847 5540
	Nawton	
	Hamilton 3200	Email: sales@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz