

Code	Description	Size	Colour
75133	Gorilla Sealant Remover Spray	400ml	Transparent

## 1. Description

Gorilla Sealant Remover Spray is a ready-to-use and fast-working spray based on terpenes for removing hardened silicones and MS polymers. Can be applied on most surfaces, including aluminium, coatings, ceramics, laminated board, paint and certain plastics.

## 2. Characteristics

- Fast-working
- Does not drip
- Specifically for silicones and MS polymers.

## 3. Technical Data

<b>Base:</b>	Mixture based on terpenes
<b>Consistency:</b>	Liquid
<b>Density:</b>	0,875g/mL
<b>Viscosity at 20°C:</b>	1400 ±600 Poise
<b>Solubility in water:</b>	Insoluble
<b>Solubility in other:</b>	Soluble in hydrocarbon

## 4. Applications

- Removal of old silicone residue
- Removal of spilled silicone or spilled MS polymers from different kind of surfaces.

## 5. Packaging

Aerosol canister of 400mL (net content)

## 6. Shelf Life

3 years in an unopened packaging stored in a cool and dry place with temperatures between +5°C and +25°C.

## 7. Application Instructions

- Surface must be dry. Apply under dry weather conditions.
- Remove hard putty first with a knife.
- Shake the canister thoroughly and apply Sealant Remover on the surface to be cleaned.
- Leave to work for at least 10 min. Wipe dry with a clean cloth.
- Repeat if necessary.
- May leave stains on porous surfaces.
- Test for adverse effects on the surface in advance.
- To improve accuracy, change white nozzle by the black one.
- Application temperature: max +30°C

**Surfaces:**

Kind: coated metals, ceramic tiles, laminated plate, painted surfaces, glass, aluminium and some synthetic materials (NOT nylon and PMMA).  
 Condition: dry  
 Preliminary treatment: none

**Remarks:**

- Sealant Remover might stain on porous surfaces.
- Due to the wide variety of possible substrates and to avoid damage to the surface, a preliminary compatibility test is recommended.

*Holdfast recommends preliminary compatibility tests on surfaces on which PU Foams have not been applied previously.*

## 8. Health and Safety Recommendation

- Take into account the usual labour hygiene.
- Make sure the area is well ventilated. Always wear gloves and goggles. In case of contact with skin, wash with water and soap.

**Remark**

*The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email [info@soudal.co.nz](mailto:info@soudal.co.nz).***

**Created:** 3 August 2023

Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	134 Kohia Drive	Phone: (07) 847 5540
	Horotiu	
	Hamilton 3288	Email: <a href="mailto:info@soudal.co.nz">info@soudal.co.nz</a>
	New Zealand	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>