

TECHNICAL DATASHEET

| Code | Description | Size | Colour |
|-------|---------------------------|-------|--------|
| 75134 | Gorilla 8 n 1 Multi Spray | 400ml | Clear |

1. Description

Gorilla 8 n 1 Multi-Spray is a high-quality universal spray with 8-fold action: rust dissolver, lubricant, cleaner, water-repellent, penetrating oil, corrosion resistant, contact spray, shock spray.

2. Characteristics

- · Lubricates
- · Protects
- · Rust & Corrosion Resistant.
- · Reduces Humidity
- · Removes Dirt & Grease
- · Cooling & Shrinking Effect (Shock Spray)
- · Water Repellent
- $\cdot \,$ Does not contain silicones
- $\cdot \;$ For indoor & outdoor use
- · Aerosol can be used in any angle (360°).

3. Technical Data

| Base: | Mixture based on mineral oils |
|---------------------------------|-------------------------------|
| Consistency: | Liquid |
| Density: | 0,81g/ml |
| Viscosity at 20°C: (Brookfield) | 1 mPa.s |
| Flashpoint: | 52°C |
| Acidity Level (Text) | Neutral |
| Solubility in water: | Insoluble |
| Solubility in other: | Soluble in hydrocarbon |
| VOC: | 84% |
| Temperature Resistance: | -50°C → 190°C |

*these values may vary depending on environmental factors such as temperature, moisture and substrate type.

4. Applications

- · To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles,...
- $\cdot\,$ Is corrosion-resistant. Has a penetrating action and a protective film remains after cleaning
- · Does not attack rubber, plastics or metals

5. Packaging

Aerosol canister of 400mL (net content)

6. Shelf Life

3 years in an unopened packaging stored in a cool and dry place with temperatures between +5°C and+25°C.

7. Application Instructions

Surfaces:

Nature: Materials: Clean, free of dust & grease All types and plastics

Application Method

- $\cdot\,$ Surface must be cleaned, degreased and dry.
- · Shake can well before use.
- $\cdot\,$ Use spray can at a distance of approx. 20cm of the object.
- · Apply as required
- · Switch electrical installations back on once the spray has evaporated.
- $\cdot\,$ When using as a rust dissolver, wait 5-10 minutes.
- $\cdot\,$ Shake the canister thoroughly and apply Sealant Remover on the surface to be cleaned.
- $\cdot\,$ Leave to work for at least 10 min. Wipe dry with a clean cloth.
- · Repeat if necessary.
- · May leave stains on porous surfaces.
- $\cdot\,$ Test for adverse effects on the surface in advance.
- $\cdot\,$ To improve accuracy, change white nozzle by the black one.
- · Application temperature: max +30°C

Remarks:

- · Gorilla 8 n 1 Multi-Spray might stain on porous surfaces.
- · Due to the wide variety of possible substrates and to avoid damage to the surface, a preliminary compatibility test is recommended.

Soudal recommends preliminary compatibility tests on surfaces on which Gorilla 8 n 1 Multi Spray has not been applied previously.

8. Health and Safety Recommendation

- · Take into account the usual labour hygiene.
- · Make sure the area is well ventilated. Always wear gloves and goggles. In case of contact with skin, wash with water and soap.

Remark

The directives and data contained in this documentation is provided in good faith and accurately reflect Soudal's knowledge when its products are properly stored, handled and applied under normal conditions in accordance with Soudal's recommendations. In practice, the diversity of the materials, substrates, environments, site conditions, product storage, handling and application are such that no warranty can be given in respect to the merchantability or fit for purpose, of any product. All users must determine the product suitability for their purposes through testing. This technical data sheet and product properties may change without notice so users, suppliers and retailers of Soudal products should always check that the data sheets they have are the latest. To the maximum extent permitted by law, Soudal disclaims all warranties in relation to either the manufacture, storage and end use of the product. All orders are accepted subject to our current terms of trade. **If any clarification is required, please contact Soudal Technical Services or email sales@soudal.co.nz**.

Created: 29 July 2019

| Supplier contact details: | Soudal Ltd | Freephone: 0800 70 10 80 |
|---------------------------|-----------------|----------------------------------|
| | 14 Avalon Drive | Phone: (07) 847 5540 |
| | Nawton | Fax: (07) 847 0324 |
| | Hamilton 3200 | Email: sales@soudal.co.nz |
| | New Zealand | Website: <u>www.soudal.co.nz</u> |