

Post Kit Folding Frame Clothesline

Product Manual

Congratulations

Congratulations on the purchase of your new **Sun King Folding Frame Clothesline Post Kit.** It is important that you read this Product Manual thoroughly before installation and use. In this way you will benefit from all the design features and enjoy safe use of the product. Thank you for choosing Sun King.

Warning

- Do not allow children or pets to swing on your Clothesline or items of laundry.
- Ensure when raising and lowering your Clothesline that bystanders (in particular children) are standing well clear.
- Do not use your Folding Clothesline for any purpose other than to hang and dry washing.
- Do not use your Clothesline if parts are worn or damaged.
- Do not allow the frame to lower in an uncontrolled manner as damage or injury may result.

Patents and Registered Designs apply to this product.

Please retain this Product Manual. Record the following information for future reference.

Product Number (printed on carton): _____

Date of purchase: _

Name and location of store:



Designed and tested under a Quality System that meets Hills demanding quality specifications.

Made in China



Carton contents

Part name	Qty.
Post - fixed	2
Cross brace	1
Product manual	1
Post kit accessory bag (includes):	1
2 x M8 x 75 ZP socket head screw 2 x M8 x 55 ZP socket head screw 4 x M8 ZP nyloc nuts 1 x hex key 6mm 8 x M8 washer	



M8 nyloc nut

M8 washer

Step 1 – Unpacking the Folding Frame Clothesline Post Kit

Check all components are in the carton (refer to tables above for your model).

Step 2 – Select a suitable location

- **2.1** Select a suitable location for your Post mounted Folding Frame Clothesline.
- 2.1 Ensure you have left sufficient space surrounding the Clothesline (Fig. 1). We recommend 0.1m each side and 0.75m in front.



Ensure area is free from pipes and obstructions

Product Dimensions

Product	Width (mm)	Depth (mm)
Double Folding Frame Clothesline	2250	1200
Single Folding Frame Clothesline	2250	1200

Installation

Step 3 – Installing the Post Kit

3.1 You will require the following materials and tools:

Pre-mix concrete Coarse gravel Spade Tape measure Spirit level

Post Hole Centres

Product	Centres (mm)
Double Folding Frame Clothesline	2200
Single Folding Frame Clothesline	2200

Recommended Installation Height



4

Installation

Step 4 – Installing Fixed Posts

- Having selected a suitable location, dig two holes approximately 200mm diameter x 600mm deep at hole centres to suit your product (see Post Hole Centre Chart on pg. 4). Place approximately 150mm of coarse gravel into the hole.
- **4.2** Place Posts into the hole. Push the base of the Posts into the gravel until the recommended height is achieved.

We recommend that the Spreader Bar of your Folding Frame Clothesline is installed 50mm above your typical user head height, therefore the top of the Posts must be installed 30mm above user head height (refer to diagram pg. 4).

- **4.3** Loosely fasten the Cross Brace to the top hole in each Post using the M8 x 80mm socket head bolts.
- **4.4** Support and check (using a spirit level and tape measure) that the Posts are parallel with each other and level, both vertically and horizontally.
- **4.5** Concrete Posts into position. Concrete should be damp enough to hold together when squeezed in your hand. Pack the concrete firmly and settle by poking with a thin stick. Slope the top surface of the concrete away from the Posts to provide drainage away from the Post.
- **4.6** Re-check Posts are parallel and level, then allow concrete to set thoroughly for at least 24 hours before final product assembly.



In addition to all rights and remedies to which you may be entitled under the New Zealand Consumer Guarantees Act (1993) and any other relevant legislation, Holdfast NZ Limited warrants the product to be free from defects in materials or workmanship for 10 years from the date of purchase.

In the event of a claim, you must take the product with proof of purchase and an explanation of the fault to the place of purchase or contact Holdfast NZ Limited and provide your proof of purchase. All costs associated with the return of the good (and other expenses incurred in claiming under this warranty) are your responsibility. We will, at our option, either repair or replace the product if it has a defect in its materials or workmanship.

Holdfast NZ Limited liability under this warranty is subject to Holdfast NZ Limited being satisfied that a defect was caused by defective workmanship or materials and was not caused by or substantially contributed to by other factors including (but not limited to) maintenance or repair, adjustments or modifications of the product in a manner not recommended by the manufacturers or any neglect, misuse or excessive use. For the avoidance of doubt, this warranty does not cover acts of God, earthquake, cyclone, fire, explosion, flood, landslide, lightning, storm, tempest, drought or meteor, war, terrorism, restraint or damage to property by or under the order of any government authority or industrial action.

You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

For goods purchased within New Zealand, this warranty is provided by Holdfast NZ Limited , 14 Avalon Drive, Nawton, Hamilton. Phone 0800 70 10 80.

Holdfast Contacts

HOLDFAST NZ LTD

14 Avalon Drive, SH 1, Nawton 3200 PO Box 4206, Hamilton East 3247 Hamilton, New Zealand Ph: (07) 847 5540, Fax (07) 847 0324 Free Phone: 0800 70 10 80 Email: sales@holdfast.co.nz www.holdfast.co.nz

6

8

Holdfast NZ LTD Issue August 2016

HD10288a



Right First Time.