

Section 1 Identification of Chemical Product and Company

| Code | Description | Size | Colour |
|-------|---------------------------------------|-------|--------|
| 01860 | Soudal Powercrete 7-min Repair Mortar | 10 Kg | Grey |

| | | |
|--|-----------------|---|
| Recommended use: | Mortar | |
| HSNO Group Standard | HSR002543 | |
| UN number, shipping name and packaging group: | Not Regulated | |
| Supplier contact details: | Soudal Ltd | Freephone: 0800 70 10 80 |
| | 134 Kohia Drive | Phone: (07) 847 5540 |
| | Horotiu | Fax: (07) 847 0324 |
| | Hamilton 3288 | Email: sales@soudal.co.nz |
| | New Zealand | Website: www.soudal.co.nz |
| POISON CENTRE NUMBER: 0800 764 766 (24 hours) | | |

Section 2 Hazards Identification

Statement of Hazardous Nature

This product is classified as:

HAZARDOUS SUBSTANCE according to the criteria of GHS v7.

NOT REGULATED under NZS5433:2020 Transport of Dangerous Goods on Land

GHS classification:

| Classification | GHS Hazard statements |
|---|---|
| Skin Corrosion Category 1B | H314 Causes severe skin burns and eye damage |
| Eye Corrosion Category 1 | H318 Causes serious eye damage |
| Skin Sensitisation Category 1 | H317 May cause an allergic skin reaction |
| Carcinogenicity Category 1 | H350 May cause cancer |
| STOT – RE Category 2 | H373 May cause damage to organs through prolonged or repeated exposure |
| STOT – SE RTI Category 3 | H335 May cause respiratory irritation |

HSNO Signal Word:

DANGER



Precautionary Statements:

| | |
|--|---|
| P102 Keep out of the reach of children | P271 Use only outdoors or in a well-ventilated area |
| P103 Read label before use | P264 Wash exposed external body areas thoroughly after handling |
| P202 Do not handle until all safety precautions are read and understood | P280 Wear protective gloves and protective clothing/ eye protection/ face protection |
| | P272 Contaminated work clothing should not be allowed out of the workplace |
| P260 Do not breathe dusts | |

SAFETY DATASHEET

P101 If medical advice is needed, have product container or label at hand
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
 P302+P361+P353 IF ON SKIN (or hair): Take off immediately contaminated clothing. Rinse skin with water (or shower)
 P362+P364 Take off contaminated clothing and wash it before reuse
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: get medical advice/ attention
 P304+P340 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
 P308+P313 If exposed or concerned: Get medical advice/ attention
 P310 Immediately call a POISON CENTRE/ doctor/ physician/ first aider
 P501 Dispose of contents/ container to authorised hazardous or special waste collection points in accordance with local regulation

Section 3. Composition/Information on Ingredients

| INGREDIENT | CAS No | WEIGHT % |
|--|------------|----------|
| Cement, alumina chemicals | 65997-16-2 | |
| Cement, Portland chemicals | 65997-15-1 | |
| Ingredients determined to be non-hazardous | | balance |

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non-hazardous ingredients are also possible.

Section 4 First Aid Measures

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Eye contact:

Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact:

Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.

Inhalation:

remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.

Ingestion:

For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay

Notes to physician:

Treat symptomatically.

Section 5 Fire-Fighting Measures

Extinguishing media:

There is no restriction on the type of extinguisher which may be used. Use extinguishing media suitable for surrounding area.

Fire/ Explosion Hazard:

Under certain conditions the material may become combustible because of the ease of ignition which occurs after the material reaches a high specific area ratio (thin sections, fine particles, or molten states). However, the same material in massive solid form is comparatively difficult to ignite. Nearly all metals will burn in air under certain conditions. Some are oxidised rapidly in the presence of air or moisture, generating sufficient heat to reach their ignition temperatures. Others oxidise so slowly that heat generated during oxidation is dissipated before the metal becomes hot enough to ignite. Particle size, shape, quantity, and alloy are important factors to be considered when evaluating metal combustibility. Combustibility of metallic alloys may differ and vary widely from the combustibility characteristics of the alloys' constituent elements.

Advice for fire-fighters:

Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use firefighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.

Section 6 Accidental Release Measures

Minor Spills:

Clean up all spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust. Sweep up, shovel up or Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Place spilled material in clean, dry, sealable, labelled container.

Major Spill

Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise Emergency Services.

Section 7 Handling and Storage

Handling:

Avoid skin contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to come in direct contact with human skin or eyes. DO NOT allow material to come in contact with exposed food or food contact surfaces. Suitable PPE must be worn at all times. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained

Storage:

Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Suitable Container:

Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.

Section 8 Exposure Controls/Personal Protection

Exposure Limits

| CAS no. | Substance or ingredient | WES-TWA | WES-STEL |
|------------|---------------------------|--|----------|
| 65997-16-2 | Cement alumina chemicals | 10 mg/m ³ inhalable 3 mg/m ³ respirable | |
| 65997-15-1 | Cement portland chemicals | 3 mg/m ³ inhalable 1 mg/m ³ respirable | |

SAFETY DATASHEET

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Engineering Controls:

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Exposure controls:

| Control | Protective measure |
|-------------|--|
| Eye | Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. |
| Respiratory | Not normally required. Where inadequate ventilation exists then a Type-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent) |
| Skin | Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety footwear. OTHERWISE: Overalls. Skin cleansing cream. Eyewash unit. Do not spray on hot surfaces. |

Section 9 Physical and Chemical Properties

General substance properties:

| Property | Details |
|------------------------|-------------------|
| Appearance | Powder |
| Colour | Grey |
| Odour | Not available |
| pH | 7 |
| Vapour pressure | No data kPa |
| Vapour Density | Not applicable |
| Viscosity | Not available |
| Boiling Point | Not applicable °C |
| Volatile materials | No data % |
| Freezing/melting point | Not available |
| Water Solubility | Miscible |

| | |
|--|--|
| Specific gravity/density | No data g/ml |
| Flash point | Not available |
| Evaporation Rate | No data BuAC = 1 |
| Auto-ignition temperature | Not available °C |
| Upper and lower flammability limits | Not available % LEL Not available % UEL |
| Corrosiveness | Not available |

Section 10 Stability and Reactivity

Stability:

Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.

Conditions to avoid:

Exposure to excessive heat, open flames and sparks. Avoid conditions that favour the formation of excessive mists and/or fumes. Contact with water may release flammable gases.

Incompatible materials to avoid:

Oxidising or reducing agents

Hazardous decomposition products:

Carbon monoxide (CO) carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Section 11 Toxicological Information

Summary of Toxicity

| Test | Data and symptoms of exposure |
|----------------|---|
| Inhaled | Inhalation may result in ulcers or sores of the lining of the nose (nasal mucosa), and lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. The material has NOT been classified by EC Directives or other classification systems as 'harmful by inhalation' nor has it been designated as 'irritating to the respiratory system'. This is because of the lack of corroborating animal or human evidence. Effects on lungs are significantly enhanced in the presence of respirable particles. |
| Oral | The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Ingestion may produce inflammation of the digestive tract, nausea, vomiting and abdominal pain. The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. |
| Dermal | The material can produce chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Skin contact may result in severe irritation particularly to broken skin. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. |

SAFETY DATASHEET

| | |
|----------------|--|
| | Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye | The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. |
| Chronic | Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment |

| Ingredient | Oral LD ₅₀ | Dermal LD ₅₀ | Inhalation LC ₅₀ |
|--------------------------|-----------------------|-------------------------|-----------------------------|
| ATE | | | |
| Calcium aluminate cement | >2000 mg/kg | >2000 mg/kg | 1.9 mg/L/4h |

Section 12 Ecological Information

Summary of Ecotoxicity

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high-water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

| Ingredient | Fish LC ₅₀ 96hr | Crustacea EC ₅₀ 48hr | Algae EC ₅₀ 72hr |
|--------------------------|----------------------------|---------------------------------|-----------------------------|
| ATE | | | |
| Calcium aluminate cement | > 100 mg/L | 5.4 mg/L | 3.5 mg/L |

| | Persistence Water/Soil | Persistence Air | Bioaccumulation | Mobility |
|--|------------------------|-----------------|-----------------|----------|
| | | | | |

Section 13 Disposal Considerations

Disposal methods:

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible.

Otherwise: If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction | Reuse | Recycling | Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf-life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.

Section 14 Transport Considerations

NOT REGULATED

Section 15 Regulatory Information

HSNO approval number and Group Standard:

HSR002543 Construction Products, Corrosive, Carcinogenic

Group Standard conditions and other regulations:

| Condition | Requirement |
|-----------------------------------|--|
| SDS | Required |
| Emergency plan | Required when quantities exceed 100 Kg |
| Certified handler | Not required |
| Tracking | Not applicable |
| Bunding and secondary containment | Not applicable |
| Signage | Required when quantities exceed 100 Lt |
| Location Compliance certificate | Not Required |
| Hazardous Atmosphere Zone | Not required |
| Fire extinguisher | Not required |

National Inventories

Y = All ingredients are on the inventory

National Inventories:

| | | |
|-------------|--|-----|
| Australia | AiIC <small>non-industrial use</small> | No |
| Canada | DSL | No |
| | NDSL | No |
| China | IECSC | Yes |
| EU | EINEC/ELINCS/NLP | Yes |
| Japan | ENCS | No |
| Korea | KECI | Yes |
| New Zealand | NZIOC | Yes |
| Philippines | PICCS | No |
| US | TSCA | No |
| Taiwan | TCSI | Yes |
| Mexico | INSQ | No |
| Vietnam | NCI | Yes |
| Russia | FBEPH | No |
| UAE | Control List | No |

Section 16 Other Information

Revision History:

| | |
|---------------|------------------------------------|
| May 2026 | Reviewed and reissued |
| August 2021 | Review and update to GHS v7 format |
| February 2017 | Initial preparation |

Abbreviations:

| Abbreviation | Description |
|-----------------------------|--|
| CAS number | Number assigned to chemical in the Chemical Abstracts Service registry |
| HAZCHEM code | Code used by fire-fighters to determine correct method of action in the case of fire |
| HSNO | Hazardous Substances and New Organisms (Act) |
| ICAO Technical Instructions | International Civil Aviation Organization Technical Instructions |
| LC ₅₀ | Lethal concentration 50% - concentration fatal to 50% of the tested population |

| | |
|------------------|---|
| LD ₅₀ | Lethal dose 50% - dose fatal to 50% of the tested population |
| NZS 5433:2020 | New Zealand Standard 5433 (Standard for the Transport of Dangerous Goods on Land) |
| STEL | Short term exposure limit |
| TWA | Time weighted average (typically measured as 8 hours) |
| UN number | United Nations number |
| WES | Workplace exposure standard |

References

Chemical properties and GHS classifications derived from the New Zealand chemical classification information database (CCID).
www.epa.govt.nz.

Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 15th Edition (February 2025).

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other material or in any process, unless specified in the text.

This SDS was prepared by Collievale Enterprises in accord with the Hazardous Substances (Safety Data Sheets) Notice 2020
admin@collievale.com Phone +64 7 5432428

End of SDS