

# Safety Data Sheet

# SOUDAL

## Hazardous, Dangerous Goods

### Section 1 | IDENTIFICATION OF CHEMICAL PRODUCT AND COMPANY

Code	Description	Size	Colour
175752	Soudal Roof & Gutter Silicone NC	300 ml	Clear
175795	Soudal Roof & Gutter Silicone NC	300 ml	Light Grey

<b>Recommended use:</b>		Sealant		
<b>Group Standard</b>		HSR002670		
<b>UN Number, Proper Shipping Name and Packaging Group</b>		Not applicable		
<b>Supplier Contact details</b>	<b>Soudal Pty Ltd</b>	Telephone: <b>1300 507 011</b>	<b>Soudal Ltd</b>	Freephone: <b>0800 70 10 80</b>
	75 Owen Street	ABN: 50 1591 240 53	134 Kohia Drive	Phone: 07 847 5540
	Glendenning		Horotiu	
	NSW 2761	Email: <a href="mailto:soudlinfo@soudal.com.au">soudlinfo@soudal.com.au</a>	Hamilton	Email: <a href="mailto:sales@soudal.co.nz">sales@soudal.co.nz</a>
	Australia	Website: <a href="http://www.soudal.com.au">www.soudal.com.au</a>	New Zealand	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>
<b>New Zealand POISON CENTRE NUMBER: 0800764 766(24 hours)</b>				
<b>Australia POISON CENTRE 131126</b>				
<b>Australia Emergency Telephone number: 1300 507 011</b>				

### Section 2 | HAZARD IDENTIFICATION

#### Statement of Hazardous Nature

This product is classified as: **HAZARDOUS SUBSTANCE** according to the criteria of GHS v7 & WHS Regulations.  
**NOT REGULATED** under NZS5433:2020 Transport of Dangerous Goods on Land & ADG

**Poison Schedule:** Unknown

#### Hazard Classification

<b>Eye Irritation</b>	<b>Category 2</b>
<b>Skin Sensitisation</b>	<b>Category 1</b>
<b>Carcinogenicity</b>	<b>Category 2</b>

#### Label Elements



**Signal Word** **WARNING**

<b>Hazard Statements</b>	H319	Causes serious eye irritation
	H317	May cause an allergic skin reaction
	H351	Suspected of causing cancer

# Safety Data Sheet



# SOUDAL

## Supplementary Statements

### Precautionary Statements | Prevention

P101	Keep out of reach of children
P102	Read label before use
P202	Do not handle until all safety directions have been read and understood
P261	Avoid breathing mist/ sprays/ vapours
P280	Wear protective gloves, protective clothing, eye protection and face protection
P272	Contaminated work clothing should not be allowed out of the workplace
P264	Wash all exposed external body areas thoroughly after handling

### Precautionary Statements | Response

P301+P312	IF SWALLOWED: Immediately call a POISON CENTRE/ Doctor/ Physician/ First Aider if you feel unwell
P303+P362	IF ON SKIN: Wash with plenty of water and soap
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P304+P340	IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
P312	Call a POISON CENTRE/ Doctor/ Physician/ First Aider if you feel unwell

### Precautionary Statements | Storage

P405	Store locked up
------	-----------------

### Precautionary Statements | Disposal

P501	Dispose of contents/ containers in accordance with local regulations
------	--

## Section 3 | COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	CAS No	WEIGHT %
2-Butanone oxime	96-29-7	< 3
Pyrithione zinc	13463-41-7	< 0.1
Ingredients determined to be non-hazardous		balance

This is a commercial product whose exact ratio of components may vary slightly. Quantities of other non-hazardous ingredients are also possible.

## Section 4 | FIRST AID MEASURES

### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 131126 from anywhere in Australia or 0800 7674766 from anywhere in New Zealand and is available at all times. Have this SDS or product label with you when you call.

**NZ EMERGENCY SERVICES: 111**

**AUSTRALIAN EMERGENCY SERVICES: 000**

### Eye contact:

Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### Skin Contact:

Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation

# Safety Data Sheet



# SOUDAL

## Inhalation:

Remove from contaminated area. Other measures are usually unnecessary.

## Ingestion:

Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

## Notes to physician:

Treat symptomatically.

## Section 5 | FIRE FIGHTING MEASURES

### Suitable extinguishing media:

Alcohol stable foam. Dry chemical powder. Carbon dioxide. Water spray or fog - Large fires only.

### Fire and Explosion Hazards:

Combustible. Will burn if ignited.

### Special Protective Equipment and Precautions for Firefighters:

Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use

### Fire Decomposition

Combustion products include: carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material.

**Hazchem Code** not applicable

## Section 6 | ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures:

Refer Section 8

### Environmental Precautions:

Refer Section 12

### Minor Spills:

Slippery when spilt. Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water.

### Major Spills:

Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by all means available, spillage from entering drains or water courses. Consider evacuation (or protect in place). No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Contain or absorb spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

## Section 7 | HANDLING & STORAGE

### Handling:

Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### Storage:

Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from

# Safety Data Sheet

# SOUDAL

incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS

### Suitable Container:

Packing as supplied by manufacturer. Aerosol dispenser. Check that containers are clearly labelled.

### Storage Incompatibility:



+

X

+

X

+

+

+

X Must not be stored together

0 May be stored together with specific precautions

+ May be stored together

## Section 8 | EXPOSURE CONTROLS AND PERSONAL PROTECTION

### National Occupational Exposure Limits:

#### New Zealand

TWA (mg/m<sup>3</sup>) STEL (mg/m<sup>3</sup>)

#### Australia

TWA (mg/m<sup>3</sup>) STEL (mg/m<sup>3</sup>)

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Biological Limit Values:

As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do have a Biological Limit Allocated.

### Engineering Measures:

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be 98-54-4 independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

### Personal Protection Equipment:

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS 2919**, Industrial Eye Protection: **AS 1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS 2210**.

### Eye Protection:

Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

# Safety Data Sheet



# SOUDAL

## Skin Protection:

Wear chemical protective gloves, e.g. Neoprene or Nitrile. Wear safety footwear or safety gumboots, e.g. Rubber Overalls. PVC Apron. PVC protective suit may be required if exposure severe.

## Respiratory Protection:

Not normally required. Where inadequate ventilation exists then a Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Thermal Protection:

Not required

## Hygiene measures:

Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 9 | PHYSICAL & CHEMICAL PROPERTIES

<b>Physical State:</b>	Paste
<b>Colour:</b>	Coloured
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	No data
<b>Freezing/ Melting Point/Range (°C):</b>	Not available
<b>Boiling Point/Range (°C):</b>	Not available
<b>Flammability:</b>	Highly flammable
<b>Lower Explosive Limit (%):</b>	Not available
<b>Upper Explosive Limit (%):</b>	Not available
<b>Flash Point (°C):</b>	Not available
<b>Autoignition Temp (°C):</b>	Not available
<b>Decomposition Temp (°C):</b>	Not available
<b>SADT (°C):</b>	Not applicable
<b>pH:</b>	Not applicable
<b>Dynamic viscosity:</b>	Not available
<b>Kinematic viscosity:</b>	Not available
<b>Water Solubility:</b>	Immiscible
<b>Solubility:</b>	Not available
<b>Coeff Octanol/ water distribution:</b>	Not available
<b>Vapour Pressure (kPa):</b>	Not available
<b>Specific Gravity (g/cm<sup>3</sup>):</b>	1.18
<b>Relative Vapour Density:</b>	Not available
<b>Volatiles (%):</b>	Not available
<b>Total VOC:</b>	2 %
<b>Evaporation Rate:</b>	Not available
<b>Explosive Properties:</b>	No chemical group associated with explosive properties
<b>Oxidising Properties:</b>	No chemical group associated with oxidizing properties
<b>Corrosive Properties:</b>	No chemical group associated with corrosive properties

## Section 10 | STABILITY & REACTIVITY

### Reactivity:

Refer Section 7

### Chemical Stability:

Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerization will not occur.

# Safety Data Sheet

  
**SOUDAL****Conditions to Avoid:**

Refer Section 7

**Incompatibilities:**

Refer Section 7

**Polymerisation:**

This product will not undergo polymerization reactions

**Hazardous Decomposition Products:**

Refer Section 5

**Section 11 | TOXICOLOGICAL INFORMATION****Inhalation:**

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The major toxic effects of MEKO, regardless of the route of administration, are anaemia with breakdown of red blood cells, rapid breathing and reversible reduction in spontaneous activity, motor coordination and muscle tone. At extremely high concentrations it may cause unconsciousness and failure of breathing. Not normally a hazard due to non-volatile nature of product.

**Ingestion:**

The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.

**Skin Contact:**

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Skin application with methyl ethyl ketoxime under an occlusive dressing produced mild irritation with redness, swelling and wheals. Open cuts abraded or irritated skin should not be exposed to this material. Entry into the bloodstream through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Low molecular weight silicone fluids may exhibit solvent action and may produce skin irritation. Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin

**Eye Contact:**

This material can cause eye irritation and damage in some persons.

**Chronic Health Effects:**

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

Ingredient	Oral LD <sub>50</sub>	Dermal LD <sub>50</sub>	Inhalation LC <sub>50</sub>
ATE			
2 Butanone oxime	160 mg/Kg	100 mg/Kg	0.14 mg/L/4hr

**Classification**

Acute Oral Toxicity	not classified
Acute Dermal Toxicity	not classified
Acute Inhalation Toxicity	not classified
Skin Corrosion/Irritation	not classified
Eye Corrosion/Irritation	Category 2
Respiratory Sensitisation	not classified
Skin Sensitisation	Category 1

# Safety Data Sheet

# SOUDAL

Germ Cell Mutagenicity	not classified
Carcinogenicity	Category 2
Reproductive Toxicity	not classified
STOT – SE	not classified
STOT – RE	not classified
Aspiration Hazard	not classified

## Section 12 | ECOLOGICAL INFORMATION

Ingredient	Fish	Crustacea	Algae
ATE			
2-Butanone oxime	LC <sub>50 96hr</sub> 100 mg/L	EC <sub>50 48hr</sub> 201 mg/L	EC <sub>50 72hr</sub> 6.09 mg/L
Zinc Pyrithione	LC <sub>50 96hr</sub> 0.003 mg/L	EC <sub>50 48hr</sub> >0.002 mg/L	EC <sub>50 72hr</sub> 0.001 mg/L

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high-water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites. DO NOT discharge into sewer or waterways.

	Persistence Water/Soil	Persistence Air	Bioaccumulation	Mobility
2-Butanone oxime	LOW	LOW	LOW	LOW
Zinc Pyrithione			LOW	

## Section 13 | DISPOSAL CONSIDERATIONS

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible.

Otherwise: If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction | Reuse | Recycling | Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf-life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.

## Section 14 | TRANSPORT CONSIDERATIONS

NOT REGULATED

## Section 15 | REGULATORY INFORMATION

**HSNO approval number and Group Standard:**

**HSR002679 Surface Coatings & Colourants Carcinogenic**

Condition	Requirement
SDS	Required

# Safety Data Sheet



# SOUDAL

<b>Emergency plan</b>	Required when quantities exceed 100 Lt
<b>Certified handler</b>	Not required
<b>Tracking</b>	Not applicable
<b>Bunding and secondary containment</b>	Required dependent upon total quantity and pack size
<b>Signage</b>	Required when quantities exceed 100 Lt
<b>Location Compliance certificate</b>	Not required
<b>Hazardous Atmosphere Zone</b>	Not applicable
<b>Fire extinguisher</b>	Not applicable

## National Inventories:

Australia AIC	non-industrial use	Yes
Canada	DSL	Yes
	NDSL	No
China	IECSC	Yes
EU	EINEC/ELINCS/NLP	No
Japan	ENCS	Yes
Korea	KECI	Yes
New Zealand	NZIOC	Yes
Philippines	PICCS	Yes
US	TSCA	Yes
Taiwan	TCSI	Yes
Mexico	INSQ	No
Vietnam	NCI	Yes
Russia	FBEPH	No

## This material is not subject to the following international agreements:

Montreal Protocol	Ozone Depleting Substances	Not applicable
Stockholm Convention	Persistent Organic Pollutants	Not applicable
Rotterdam Convention	Prior Informed Consent	Not applicable
Kyoto Protocol	Greenhouse Gases	Not applicable
Basel Convention	Hazardous Waste	Not applicable

## Section 16 | OTHER INFORMATION

### Revision History (valid for five years)

June 2025	Combined SDS format
November 2024	Origination

**This SDS contains only safety-related information. For other data see product literature.**

Please read all labels carefully before using product.

### Acronyms:

<b>AICIS</b>	Australian Inventory of Industrial Chemicals
<b>ADG</b>	Australian Dangerous Goods
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially fire-fighters.
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>STEL</b>	Short term Exposure Limit
<b>TWA</b>	Time Weighted Average
<b>UN Number</b>	United Nations Number
<b>WES</b>	Workplace Exposure Standard

# Safety Data Sheet



## References

Chemical properties and GHS classifications derived from the New Zealand chemical classification information database (CCID).  
[www.epa.govt.nz](http://www.epa.govt.nz)

Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 15<sup>th</sup> Edition (February 2025).

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE BASED ON THE INFORMATION PROVIDED AT THE TIME OF ISSUE. IT IS BASED ON THE PRESENT LEVEL OF RESEARCH AND TO THIS EXTENT WE BELIEVE IT IS ACCURATE. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED AND SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, ALL INFORMATION RELEVANT TO USAGE IS OFFERED WITHOUT WARRANTY. THE MANUFACTURER/ SUPPLIER WILL NOT BE HELD RESPONSIBLE FOR ANY UNAUTHORISED USE OF THIS INFORMATION OR FOR ANY MODIFIED OR ALTERED VERSIONS.

EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY, SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

SAFETY DATASHEETS ARE UPDATED FREQUENTLY, PLEASE ENSURE THAT YOU HAVE A CURRENT COPY.

This SDS was prepared by Collievale Enterprises Ltd in accord with the Safe Work Australia – Preparation of safety datasheets for hazardous chemicals Code of Practice July 2020 and the Hazardous Substances (Safety Data Sheets) Notice 2020  
[admin@collievale.com](mailto:admin@collievale.com) Phone +64 7 5432428

End of SDS