



# Color spray Marker

## Product description

Quick drying acrylic paint, firm adhesion to surfaces and resistance to friction.

## Properties

- Fast drying
- Very good adhesion on many materials
- Resistant to friction
- Can be painted
- Patented child-proof safety cap
- Aerosol can be used in any angle (360°)

## Applications

- Ideal for mapping, marking or delineating spaces, areas, corridors in works, workshops, roads, parking lots, sports facilities.



## Technical data

Consistency	Liquid
Curing system	Physical drying
Drying time	Dust dry after 10 min, tack-free after 20 min. Fully dried after 24 hours.
Application temperature	5°C → 35°C
Temperature resistance	+120°C
Yield	1,8 → 2,5m <sup>2</sup>
Solid content	18% → 23,8%

## Substrates

- Substrate condition  
The surface must be rigid, clean, dry, free of dust and grease.
- Substrate preparation  
Remove rust. We recommend a preliminary adhesion test on every surface.
- Substrate types  
Color Spray Marker Paint has a good adhesion to following substrates: all usual building substrates.

## Application method

- Application method  
Apply on dry and grease-free surface, remove old, loose paint and rust first. Shake can well before use. Spray at a distance of appr. 20 cm of the object. Shake the canister thoroughly before applying each layer.

## Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.  
Use only in well-ventilated areas.

## Packaging/Logistics

Colour: Various colours available. Please consult the product catalogue, the Soudal website or a Soudal representative.



# Color spray Marker

Packaging: Please consult the product catalogue, the Soudal website or a Soudal representative.

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

## Remarks

- After use, spray the aerosol can upside down for about 3 seconds to clean the valve until only propellant comes out. Thus avoiding the valve becomes blocked with solid residues.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.